

600-1	60	0-2 j	600-3	600-4	600-5	600-6	600-7
PRODU ID COI		OP CODE	OFFSET	DATA 0	DATA 1	DATA 2	DATA 3

600

## FIG.6A

## OPTIONS (OFFSET) TABLE


- A. COMMUNICATIONS OPTIONS
  - 1. RS-232
  - 2. BAUD RATE
  - 3. RF LINK
  - 4. ETHERNET
- B. CODE OPTIONS
  - 1. DISABLE 1D
  - 2. DISABLE 2D
  - 3. DISABLE INDIV.
  - 4. MIN-MAX LENGTH
  - 5. MULTIPLE SYMBOLS ENABLED
- C. SCANNING-DECODING OPTIONS
  - 1. ONE SHOT
  - REPEAT UNTIL DONE
  - 3. REPEAT UNTIL STOPPED
  - 4. SCAN ON DEMAND
  - 5. SKIP SCAN
  - 6. DECODE ON DEMAND
- D. OPERATING OPTIONS
  - 1. BEEPER VOLUME
  - 2. AIMING LED ON/OFF
  - 3. AURAL FEEDBACK
- E. TRANSMIT OPTIONS
  - SEND CHECK CHAR'S
  - 2. SEND CHECKSUM
  - 3. DATA EDIT OPTIONS
- F. READER MODE OPTIONS
  - 1. AUTOMATIC
  - SEMI—AUTOMATIC
  - 3. BAR CODE SCANNING
  - 4. OCR
  - SIGNATURE
  - 6. COLOR IMAGING


## OP CODE TABLE


- A. OP CODE "O"-VECTOR PROC.
  - 1. OUTPUT VERSION OF SOFTWARE
  - 2. OUTPUT CONTENTS OF PARAMETER TABLE
  - 3. DISPLAY ENABLED CODES
  - 4. PRINT PARAMETER TABLE AS BAR CODE SYMBOL
- B. OP CODE "1" CLEAR
- C. OP CODE "2" SET
- D. OP CODE "3" TOGGLE
- E. OP CODE "4" ADD
- F. OP CODE "5" DEFAULT
- G. OP CODE "6" LOAD
- H. OP CODE "7" RESERVED


## FIG.6C

FIG.6B












FIG.11





FIG.12



7 1600	ERROR CHECK		ſ1602	ERROR CHECK	71604
	IMAGE DATA ER			PACKET NO.	
	IMAGE			NO. OF PACKETS	
	IMAGE TYPE	FIG.16A		TOTAL LENGTH	
	LENGTH		HEADER PACKET	HEADER ID	
	SEQUENCE NUMBER		里 /4	LENGTH	REMAINING PACKETS
				SEQUENCE	
	SCANNER ADDRESS			SCANNER ADDRESS	

FIG. 16B

ERROR CHECK

IMAGE DATA

PACKET NO.

IMAGE TYPE

LENGTH

SEQUENCE NO.

SCANNER ADDRESS

